





DURAN®

RANGE OF VOLUMETRIC FLASKS



Product Range		DURAN® VOLUMETRIC FLASKS, CLEAR					DURAN® VOLUMETRIC FLASKS, AMBER	
Accuracy class		Class A				Class B	Class A	
DURAN® glass volumetric flasks body								
Certificate*		Batch certificate	Batch certificate **	Individual certificate	Individual certificate, USP <31> conformity	–	Batch certificate	Individual certificate
Maximum recommended temperature without affecting accuracy (at 20 °C)		250 °C	250 °C	250 °C	250 °C	250 °C	250 °C	250 °C
Temperature resistance PE Stopper		–40 °C to +80 °C	–40 °C to +80 °C	–40 °C to +80 °C	–40 °C to +80 °C	–40 °C to +80 °C	–40 °C to +80 °C	–40 °C to +80 °C
Print color		Blue	White	Blue	Blue	White	White	White
ml	Stopper size	With new PE Stopper	With octagonal PE Stopper	With new PE Stopper	With new PE Stopper	With new PE Stopper	With new PE Stopper	With new PE Stopper
1	7 / 16	24 678 01 59	–	24 679 01 51	–	–	–	–
2	7 / 16	24 678 02 53	–	24 679 02 54	–	–	–	–
5	7 / 16	–	21 678 07 04	–	–	–	–	–
5W ¹	10 / 19	24 678 09 56	–	24 679 09 57	24 671 09 58	24 670 09 57	24 676 09 54	24 677 09 55
10	7 / 16	–	21 678 08 07	–	–	–	–	–
10 W ¹	10 / 19	24 678 10 52	–	24 679 10 53	24 671 10 54	24 670 10 53	24 676 10 59	24 677 10 51
20	10 / 19	24 678 12 58	21 678 12 03	24 679 12 59	–	24 670 12 59	24 676 12 56	24 677 12 57
25	10 / 19	24 678 14 55	21 678 14 09	24 679 14 56	24 671 14 57	24 670 14 56	24 676 14 53	24 677 14 54
50	12 / 21	24 678 17 55	21 678 17 09	24 679 17 56	24 671 17 57	24 670 17 56	24 676 17 53	24 677 17 54
100	12 / 21	24 678 24 51	21 678 24 05	24 679 24 52	–	–	24 676 24 58	24 677 24 59
100	14 / 23	24 678 25 54	21 678 25 08	24 679 25 55	24 671 25 56	24 670 25 55	24 676 25 52	24 677 25 53
200	14 / 23	24 678 32 59	21 678 32 04	24 679 32 51	24 671 32 52	24 670 32 51	24 676 32 57	24 677 32 58
250	14 / 23	24 678 36 53	21 678 36 07	24 679 36 54	24 671 36 55	24 670 36 54	24 676 36 51	24 677 36 52
500	19 / 26	24 678 44 52	21 678 44 06	24 679 44 53	24 671 44 54	24 670 44 53	24 676 44 59	24 677 44 51
1000	24 / 29	24 678 54 57	21 678 54 02	24 679 54 58	24 671 54 59	24 670 54 58	24 676 54 55	24 677 54 56
1000 W ¹	29 / 32	24 678 55 51	–	24 679 55 52	–	–	–	–
2000	29 / 32	24 678 63 59	21 678 63 04	24 679 63 51	24 671 63 52	24 670 63 51	24 676 63 57	24 677 63 58
5000	34 / 35	24 678 73 55	21 678 73 09	24 679 73 56	–	24 670 73 56	–	–

* Batch certificates also available online at www.DWK-LifeScience.com

** Without declaration of conformity | W¹ = Wide neck

DWK Life Sciences GmbH • Hattenbergstraße 10 • 55122 Mainz • Germany • www.DWK-LifeSciences.com

Phone: +49 6131 - 1445 4131 • Fax: +49 6131 - 1445 4016 • sales@DWK-LifeSciences.com

DURAN®

RANGE OF MEASURING AND MIXING CYLINDERS



Product Range		DURAN® MEASURING CYLINDERS		DURAN® MIXING CYLINDERS	
Accuracy class		Class A	Class B	Class A	Class B
DURAN® glass cylinders body					
Certificate*		Batch certificate	–	Batch certificate	–
Maximum recommended temperature without affecting accuracy (at 20 °C)		250 °C	250 °C	250 °C	250 °C
Temperature resistance PE Stopper		Not applicable	Not applicable	-40 °C to +80 °C	-40 °C to +80 °C
Print color		Blue	White	Blue	White
ml	Stopper size ¹			With new PE Stopper	With octagonal PE Stopper
5	–	21 390 07 01	21 396 07 07	–	–
10	10 / 19	21 390 08 04	21 396 08 01	24 618 08 56	21 618 08 01
25	14 / 23	21 390 14 06	21 396 14 03	24 618 14 58	21 618 14 03
50	19 / 26	21 390 17 06	21 396 17 03	24 618 17 58	21 618 17 03
100	24 / 29	21 390 24 02	21 396 24 08	24 618 24 54	21 618 24 08
250	29 / 32	21 390 36 04	21 396 36 01	24 618 36 56	21 618 36 01
500	34 / 35	21 390 44 03	21 396 44 09	24 618 44 55	21 618 44 09
1000	45 / 40	21 390 54 08	21 396 54 05	24 618 54 51	21 618 54 05
2000	45 / 40	21 390 63 01	21 396 63 07	24 618 63 53	21 618 63 07

* Batch certificates also available online at www.DWK-LifeScience.com

¹ Valid for mixing cylinders only

DWK Life Sciences GmbH • Hattenbergstraße 10 • 55122 Mainz • Germany • www.DWK-LifeSciences.com

Phone: +49 6131 - 1445 4131 • Fax: +49 6131 - 1445 4016 • sales@DWK-LifeSciences.com